

6929 N. Lakewood Avenue Tulsa, OK 74117

PUBLIC NOTICE OF NETWORK CHANGE UNDER RULE 51.329(a)

April 19, 2024

Carrier: Verizon New Jersey Inc., One Verizon Way, Basking Ridge 07920

Contact: For additional information on these planned network changes, please contact:

Lisa Thompson Global Data Network Engineering Verizon Wireline Network Operations 13100 Columbia Pike, Floor 5 Room 505 Silver Spring, MD 20904 410 375 9777

Quadre Washington Associate Director – Global Data Network Engineering Verizon Wireline Network Operations 320 St Paul Place Baltimore, MD 21202 410 259 9829

Implementation Date: On or after January 2, 2025

Planned Network Change(s) will occur at the following locations in New Jersey:

Verizon Central Office	Address	CLLI
Gloucester NJ 5ESS Switch	1190 Market Street Gloucester, NJ 08030	GLCYNJGLDS5
Camden NJ CS2K Switch	12 N. 7 TH Street Camden, NJ 08102	CMDNNJCEPS0

This notice may also be viewed at http://www.verizon.com/about/terms-conditions/network-disclosures

PLEASE NOTE:

- All references to the Gloucester NJ 5ESS switch are associated with CLLI code GLCYNJGLDS5 and will not be repeated throughout this notice.
- All references to the Camden NJ CS2K switch are associated with CLLI code CMDNNJCEPS0 and will not be repeated throughout this notice.

Description of the Planned Network Change(s):

The Verizon Gloucester NJ 5ESS switch, located at 1190 Market Street, Gloucester, NJ 08030, will be retired and removed from the network after all traffic served by this switch is migrated to the Verizon Camden NJ CS2K switch, located at 12 N. 7TH Street, Camden, NJ 08104. All traffic to be migrated includes, but is not limited to, Inter-LATA (ACCESS/FG-B-D/CLEC/IXC), wireless, and paging traffic.

Description of Reasonably Foreseeable Impact(s) of the Planned Change(s):

Competitive local exchange carriers (CLECs), interexchange carriers (IXCs, IECs), wireless carriers, and paging carriers will need to secure new trunk groups built to the Camden NJ CS2K switch or have existing trunk groups to that switch augmented. Carriers that are code holders for access connectivity in the Gloucester NJ 5ESS switch will be required to reposition the codes to the Camden NJ CS2K switch.

All ASRs for the Camden NJ CS2K switch must be received no later than October 1, 2024 to provide sufficient time to migrate the traffic described above. These direct end office trunk (DEOT) interconnections will support traffic migration for the Gloucester NJ 5ESS switch prior to its eventual decommissioning. Local Exchange Routing Guide (LERG) change effective dates will be posted prior to decommissioning of the Gloucester NJ 5ESS switch (on or after January 2, 2025). This will serve to guide interconnect re-routes of traffic for the four (4) native codes currently served by the Gloucester NJ 5ESS switch to reflect the Camden NJ CS2K switch as the new home switch. All ASRs for the Camden NJ CS2K switch must carry the project code of GLCYNJGLDS5.